

**IN THE SPECIFICATION:**

The specification as amended below with replacement paragraphs shows added text with underlining and deleted text with ~~strike~~through.

**[0014]** These and/or other aspects and advantages of the invention will become apparent and more readily appreciated from the following description of the embodiments, taken in conjunction with the accompany drawings, of which:

FIG. 1 is a perspective view of a bread maker according to one embodiment of the present invention;

FIG. 2 is a control block diagram of the bread maker in FIG. 1; ~~and~~

FIG. 3 is an enlarged sectional view of a tray sensor 30 of the bread maker in FIG. 1; and

FIG. 4 illustrates a bread maker according to another embodiment of the present invention.

**[0036]** If a user mounts the baking tray 10 and closes the door 20 when a mixing bag 11 is inserted, the sensing member 31 of the tray sensor 30 contacts the first half 14 of the baking tray 10 and is pushed away from the tray 10. Due to the movement of the sensing member 31, the operation lever 32 pivots, and the sensing switch 33 is pressed, thereby generating a sensing signal. Alternately, as shown in FIG. 4, the sensing member 31 may be provided in the baking tray 10 such that when the door 20 is closed and the baking tray 10 is mounted, the sensing member 31 makes contact with the door 20. The sensing switch 33 then generates a sensing signal.

**IN THE DRAWINGS:**

New FIG. 4 has been added to illustrated the features recited in claims 3 and 9, in order to overcome the objection to the drawings.